BEHR PREMIUM® Concrete & Masonry Bonding Primer

- Easy to Apply
- Fast Drying
- Promotes a Uniform Topcoat Finish
- Epoxy Fortified
- Penetrating Formula

Coverage: 350-500 Sq. Ft.

Dry Time: **2 Hr.** Dry to Touch. **8 Hr.** Recoat

Use Commercial Brush Cleaner for Clean-Up

Protect from Freezing

CAUTION: Surfaces may become slippery when wet. Use caution when walking on surface when moisture is present.

WHERE TO USE

Uncoated Interior or Exterior surfaces such as Concrete, Masonry, Stucco, Cinder Block and any Porous Stone or Brick. Not designed for use on wood, metal or silicone treated surfaces. Do not use on coated surfaces. Use only on porous surfaces. **NOTE: SOME SURFACES MAY APPEAR SLIGHTLY DARKER AFTER PRODUCT DRIES.**

PREPARATION †

(The following steps and products are required.) New concrete must cure for a minimum of 30 days prior to priming. Patch all holes and cracks and allow to dry. For touch-ups where surface coatings have failed, completely remove any loose or peeling paint. Do not apply over previously coated surfaces. To completely strip previous coatings, use a product such as BEHR PREMIUM® NO. 992 Concrete & Masonry Paint Stripper. For proper penetration and adhesion of primer, use a product such as BEHR PREMIUM NO. 991 Concrete & Masonry Cleaner & Etcher to clean and etch the surface. Follow all label instructions.

APPLICATION

DO NOT THIN. Stir primer thoroughly before and occasionally during application. Use product when air and surface temperatures are between 50-90°F (10-32°C). Apply using a high quality pump sprayer, 1/4" - 3/8" nap roller, nylon/polyester brush or a pad applicator.

DRY TIME

Longer dry time required in cooler temperatures and in higher humidity. Must apply a topcoat after at least 8 hours, but before 30 days.

DISPOSAL

Do not use soap and water to clean brushes or other applicators as they will become gummy. Properly dispose of all soiled rags. To recycle or properly dispose of product in your community, contact your household refuse collection service.

† WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

WARRANTY

- Visit www.Behr.com for complete warranty information.

WARNING! This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

WARNING! IRRITANT! HARMFUL IF SWALLOWED. CONTAINS: ETHYLENE GLYCOL. MAY CAUSE EYE, NOSE AND THROAT IRRITATION. AVOID CONTACT WITH SKIN AND EYES AND AVOID BREATHING OF VAPORS AND SPRAY MIST. WEAR EYE PROTECTION AND PROTECTIVE CLOTHING. USE ONLY WITH ADEQUATE VENTILATION. To avoid breathing vapors and spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air. If properly used, a respirator (NIOSH approved for organic vapor with P series particulate pre-filter) may offer additional protection; obtain professional advice before using. A dust mask does not provide protection against vapors. Avoid contact with eyes and skin. Wash thoroughly after handling. Close container after each use. **FIRST AID:** If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact, flush immediately with plenty of water for at least 15 minutes and get medical attention; for skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately.

CAUTION: KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY.

To consult with a Behr Certified Coatings Professional, call 1-800-854-0133 Ext. 2 (U.S.A. only).

BEHR
A Masco Company

©2013 Behr Process Corporation
Santa Ana, CA 92704 U.S.A. • behr.com
V.O.C. (C.O.V.) <100 g/L • REV. 3/13